

DISHWASHER

DISHWASHER WITH TOUCH CONTROL PANEL

OBY 50T PDRT 075T.11110.AD

- User friendly new touch Control Panel
- Following washing steps easily with coloured and dynamic graphics
- Adjusting rinse aid and detergent time from touch screen.
- Adjusting water level from screen.
- Following temperature and error from display
- Stainless steel body, washing and boiler tank
- Washing tank with round corners - Hygenic
- Maximum capacity 35 rack/hr
- 2.1 lt water consumption per cycle
- 5 Washing Programmes
- Suitable for corner or in-line installation
- PP polypropylene washing arms
- Contains stainless steel tank filter.
- Adjustable feet for height optimization
- Easy start up: single button for water filling and heating in the boiler tank
- Electrical components and wiring according to international standarts and security regulations
- Thermostop-controlled, washing and rinsing temperatures for efficient washing
- Non-return - Check valve System
- Washing temperature at 55-60°C (water supply at a minimum of 2 bar and 50°C)
- Rinsing temperature at 80-85°C (water supply at a minimum of 2 bar and 50°C)



STANDARD EQUIPMENT	
DETERGENT DISPENSER	✓
RINSE AID DISPENSER	✓
RINSING PUMP	✓
DRAIN PUMP	✓
BASKETS PROMOTIONAL	2 PIECES

TECHNICAL FEATURES			
Electric Connection	230V~NPE / 50Hz	Rinsing Pump Power	0,25 kW
Total Rating	5.5 kW	Water Inlet Pressure / Temp.	2-4 Bar / 50 °C
Washing Capacity (plate/hr)	560 (Max.)	Heat Power (Washing/Rinsing)	2 / 5 kW
Washing Capacity (basket/hr)	35 / 27 / 23 / 20 / 18	Dirty Water Discharge Connection	3/4 " (Ø 28 mm)
Washing / Boiler Tank Capacity	27 / 6 lt	Maximum Noise	75 dBA
Washing Program Number	5	Gross Weight	70 (±5) kg
Program Times (seconds)	102 / 132 / 152 / 172 / 192	Dimensions (WxDxH)	595x650x830mm
Washing Water Temp.	55-60°C	Protection Class	IPX5
Rinsing Water Temp.	80-85 °C (max.)	Rack Dmension	50 x 50 cm
Water Inlet Connection	3/4 "	Useful Loading Height	335 mm
Washing Pump Power	0.66 kW	Inclination	6°

HOOD TYPE DISHWASHER

DISHWASHER WITH
TOUCH CONTROL PANEL

OBM 1080T PDRT

071T.11110.BB



- User friendly new touch Control Panel
- Following washing steps easily with coloured and dynamic graphics
- Adjusting rinse aid and detergent time from touch screen.
- Adjusting water level from screen.
- Following temperature and error from display
- Stainless steel body, washing and boiler tank
- Monoblock washing tank with round corners - Hygenic
- Maximum capacity 69 rack/hr
- 2.1 lt water consumption per cycle
- 5 Washing Programmes
- PP polypropylene washing arms
- Adjustable feet for height optimization
- Easy start up: single button for water filling and heating in the boiler tank
- Electrical components and wiring according to international standarts and security regulations
- Thermostop-controlled, washing and rinsing temperatures for efficient washing
- Non-return - Check valve System
- Washing temperature at 55-60°C (water supply at a minimum of 2 bar and 50°C)
- Rinsing temperature at 80-85°C (water supply at a minimum of 2 bar and 50°C)

STANDARD EQUIPMENT	
DETERGENT DISPENSER	✓
RINSE AID DISPENSER	✓
RINSING PUMP	✓
DRAIN PUMP	✓
BASKETS PROMOTIONAL	3 PIECES

TECHNICAL FEATURES			
Electric Connection	400V~3NPE / 50Hz	Rinsing Pump Power	0,25 kW
Total Rating	9.66 kW	Water Inlet Pressure / Temp.	2-4 Bar / 50 °C
Washing Capacity (plate/hr)	1108 (Max.)	Heat Power (Washing/Rinsing)	2 / 9 kW
Washing Capacity (basket/hr)	69 / 35 / 27 / 23 / 18	Dirty Water Discharge Connection	3/4 " (Ø 28 mm)
Washing / Boiler Tank Capacity	23 / 7 lt	Maximum Noise	120 dBA
Washing Program Number	5	Gross Weight	70 (±5) kg
Program Times (seconds)	52 / 102 / 132 / 152 / 192	Dimensions (WxDxH)	700x785x1480 (1960) mm
Washing Water Temp.	55-60°C	Protection Class	IPX5
Rinsing Water Temp.	80-85 °C (max.)	Rack Dmension	50 x 50 cm
Water Inlet Connection	3/4 "	Useful Loading Height	445 mm
Washing Pump Power	0.66 kW	Inclination	6°